

LINE 50 smooth COLOR


LINE is a product designed to be integrated directly into the system.
The LED contained in a tubular glass, available in the smooth or striped finitura, ensures an all-round light. The contacts at the ends allow you to install it directly to the system or connect several lamps in series.

TECHNICAL SPECIFICATIONS

Standard	Directive 2014/35/UE EN 60598-1 EN 60598-2-1 Directive 2011/65/UE EN 50581
Material	Diffuser in smooth borosilicate glass Fittings in galvanized steel
Treatment	Powder coating
Voltage	24 V
Wattage	10 W
Temperature	2700 K 3000 K
Lumen	912 lm 960 lm
Color rendering	80+/90+
Protection grade IP	IP67
Fire resistance	V1
Impact resistance	IK02 (IK grade according IEC/EN 62262)
Operating temperature	-20°C - +50°C
Driver	24 V DC - min. 15W


LS50-Color

Dimensions (mm)
Ø 22 - L 50



LINE section

1. borosilicate glass Ø 22
2. silicone tube
luminous surface Ø 18
3. flexural and
tensile resistant
4. light board
5. lamp board



AVAILABLE COLORS



LINE 100 smooth COLOR

LINE is a product designed to be integrated directly into the system.
The LED contained in a tubular glass, available in the smooth or striped finitura, ensures an all-round light. The contacts at the ends allow you to install it directly to the system or connect several lamps in series.

TECHNICAL SPECIFICATIONS

Standard	Directive 2014/35/UE EN 60598-1 EN 60598-2-1 Directive 2011/65/UE EN 50581
Material	Diffuser in smooth borosilicate glass Fittings in galvanized steel
Treatment	Powder coating
Voltage	24 V
Wattage	20 W
Temperature	2700 K 3000 K
Lumen	1825 lm 1920 lm
Color rendering	80+/90+
Protection grade IP	IP67
Fire resistance	V1
Impact resistance	IK02 (IK grade according IEC/EN 62262)
Operating temperature	-20°C - +50°C
Driver	24 V DC - min. 15W

LS100-Color

Dimensions (mm)
Ø 22 - L 100



LINE section

1. borosilicate glass Ø 22
2. silicone tube
luminous surface Ø 18
3. flexural and
tensile resistant
4. light board
5. lamp board

