


## FLEXIBLE CURVE FITTING COLOR

Genuit flexible curve fitting with simple crimping, guarantee excellent impact resistance, ensure in case of dispersion, thanks to the relative connections, the electrical continuity up to the grounding present inside the Genuit boxes.


### TECHNICAL SPECIFICATIONS

Characteristics	Resistance to mechanical shock, crushing, abrasion, and constriction. Excellent flexibility. Like all corrugated tubes, this flexible one has the characteristic of being able to elongate and shorten axially
Material	Carbon Steel EN10346DX51D
Treatment	pOWDER COATING
Construction	Wrapping and crimping of pre-profiled tape
Protection grade IP	IP40 - IP67
Dimensional field	From DN 22 mm
Profil	
Usage	Extremely flexible non-hermetic mechanical protection for electrical cables, optical fibers, and flexible tubes
Storage temperature	-50°C - +90°C
Operating temperature	Up to 250°C for galvanized steel. Up to 700°C for stainless steel



### RCF90 Color


Dimensions (mm)  
Ø22e (19i) x 1000 L.



### COLORS AVAIIABLE



Black  
RAL 9005



White  
RAL 9010



Blue  
RAL 5001



Green  
RAL 6016



Coral  
RAL 2012



Sand  
RAL 6016

