

LINE 50 PARALLEL - COLOR


LINE Parallel has been designed to illuminate spaces with elegance and precision. The LED, housed in a tubular polycarbonate diffuser, provides uniform all-around lighting with 360° illumination. Available in four variants, Line Parallel ensures a discreet and clean result, suitable for all types of environments.

TECHNICAL SPECIFICATIONS

Dimensions (mm)
Ø 22 - L 50


Material	Diffuser in polycarbonate Fittings in galvanized steel
Treatment	Powder coating
Voltage	24 V
Wattage	9,6 W
Temperature	2700 K 3000 K
Lumen	1348 lm 1418 lm
Color rendering	80+/90+
Protection grade IP	IP20
Fire resistance	V1
Impact resistance	IK07
Operating temperature	-20°C - +50°C
Driver	24 V DC

AVAILABLE COLORS



LINE section

1. Polycarbonate Ø 22
2. silicone tube
luminous surface Ø 18
3. flexural and
tensile resistant
4. light board
5. lamp board




LINE 100 PARALLEL - COLOR

LINE Parallel has been designed to illuminate spaces with elegance and precision. The LED, housed in a tubular polycarbonate diffuser, provides uniform all-around lighting with 360° illumination. Available in four variants, Line Parallel ensures a discreet and clean result, suitable for all types of environments.

TECHNICAL SPECIFICATIONS


Material	Diffuser in polycarbonate Fittings in galvanized steel
Treatment	Powder coating
Voltage	24 V
Wattage	9,6 W
Temperature	2700 K 3000 K
Lumen	1348 lm 1418 lm
Color rendering	80+/90+
Protection grade IP	IP20
Fire resistance	V1
Impact resistance	IK07
Operating temperature	-20°C - +50°C
Driver	24 V DC

Dimensions (mm)
Ø 22 - L 100



LINE section

1. Polycarbonate Ø 22
2. silicone tube
luminous surface Ø 18
3. flexural and
tensile resistant
4. light board
5. lamp board



AVAILABLE COLORS



Black RAL 9005 White RAL 9010 Coral RAL 2012 Sand RAL 6016



Crock RAL 8004 Sage RAL 6011 Graphite Corten

